

## Santo Domingo

|                            |                             |                         |
|----------------------------|-----------------------------|-------------------------|
| <b>Tuft gauge</b>          | 1/10 cut pile               | ISO 2424                |
| <b>Pilecomposition</b>     | 100% PES                    | ISO 2424                |
| <b>Primary Backing</b>     | Woven                       | ISO 2424                |
| <b>Secondary backing</b>   | AB                          | ISO 2424                |
| <b>Width</b>               | 400 cm, 500 cm              | ± 1%<br>EN 984          |
| <b>Pile Weight</b>         | 2350 gr/m <sup>2</sup>      | ISO 8543                |
| <b>Total weight</b>        | AB : 3160 gr/m <sup>2</sup> | ± 15%<br>ISO 8543       |
| <b>Pile height</b>         | 14 mm                       | ± 2 mm<br>ISO 1766      |
| <b>Total Height</b>        | AB : 16 mm                  | ISO 1765                |
| <b>Number of knots</b>     | 158000 /m <sup>2</sup>      | -7.5% .+10%<br>ISO 1763 |
| <b>Fire Classification</b> | Cfl-S1                      | EN 13501-1              |
| <b>Use Area</b>            | Heavy domestic use (23)     | EN 1307                 |
| <b>GUT Nr.</b>             | CAFB223E                    | www.pro-dis.info        |
| <b>Light fastness</b>      | ≥ 5                         | 105-B02                 |
| <b>Weareability</b>        | ≥ 4                         | 105-X12                 |
| <b>Water fastness</b>      | ≥ 4                         | 105-E01                 |

## Floorsymbols



## Certificates

